

# SP 4800 HST



## AC TRACTORS

New isodiametric, mono-directional model with hydrostatic transmission and an articulated chassis. Equipped with a Yanmar 3-cylinder 38hp engine - **Stage 5**. It is a compact vehicle supplied with a “full optional” cab. The articulated **ACTIO™** chassis ensures agility and manoeuvrability in confined spaces for maintenance works on footpaths and narrow streets, in snow clearing and in slaloms on ski slopes along with grass mowing in parks and gardens. It can be equipped with front and rear implements thanks to the loading bed on the bonnet.

ANTONIOCARRARO.COM



ECCELLENZA ITALIANA

# TECHNICAL DATA: SP 4800

**Frame** ACTIO™ integral oscillating frame • Unidirectional • Articulated • 4 equal-size driving wheels

**Engine type** Supercharged direct injection diesel common rail Turbo  
Emissions Standard: **Stage 5**  
N. of cylinders: 3  
Rated rpm: 2600  
Tank capacity (litres): 27

Power kW/CV (97/68/CE): 28,5/ 38,7  
Max torque (Nm/rpm): 126/1690

**Transmission** Hydrostatic with hydraulic control

**PTO** Independent, mechanical control, standard 540 rpm and synchronised groundspeed

**Shaft** splined ASAE 1" 3/8

**Hydraulic system** Basic hydraulic system controlled by double-speed joystick, consisting of 2 double-acting spool valves with floating position at front, 1 replicated at rear, flow control valve for hydraulic motor (rear hydraulic plug added) and 1 oil return at rear (total 4 quick-release couplings at front and 4 at rear, total 8 quick-release couplings)

**Rear power lift** Front hydraulic double-acting, double-speed lift and lowering, joystick-controlled; lifting capacity 1100 kg;  
Fixed lifting arms cat.1 and 1N with connecting spring;  
Front and rear EEC tow hook.

**Steering** Hydraulic power steering with 2 cylinders and Load Sensing system

**Brakes** Service brake, hydraulic type, foot operated on rear wheels. (opt. on all wheels) - Parking brake, mechanical type with lever control, acting on rear wheels

**Weight** In running order with driver: 1430-1540 Kg

**Tyres** 240/70R15 | 29X12.5-15 NHS PR6 | 29X12.5-15 | 6.5-16 8 PR

**Dimensions** With wheels 240/70R15

